



**<21 km**  
Range per Charge



**136 kg**  
Weight Capacity



**116.2 cm**  
Turning Radius



**GO GO**  
**ELITE TRAVELLER® PLUS**

## Portable Convenience

Perfect for travelling, PLUS so much more! The Go Go Elite Traveller® Plus keeps you moving through all of life's adventures, while offering feather-touch disassembly, an ergonomic tiller with wraparound handles, and black, non-scuffing tyres. Featuring a robust 17Ah battery and supporting 147 kg weight capacity it is the perfect combination of style and performance for your on-the-go lifestyle.





Easily Removable Battery Box



Feather Touch Dissassembly



Delta Tiller with Wraparound Handles

|                                          |                                                         |
|------------------------------------------|---------------------------------------------------------|
| RANGE PER CHARGE (MAX) <sup>1</sup>      | Up to 21 km                                             |
| MAXIMUM WEIGHT CAPACITY                  | 136 kg                                                  |
| TURNING RADIUS                           | 116.2 cm                                                |
| MAXIMUM SPEED <sup>1</sup>               | 7.2 km/h                                                |
| LENGTH & WIDTH <sup>3</sup>              | L: 102.3 cm W: 54 cm                                    |
| SEAT TYPE<br>WIDTH & DEPTH<br>(STANDARD) | Compact, foldable seat<br>W: 43 cm (17") D: 43 cm (17") |
| SEAT-TO-DECK<br>HEIGHT                   | 41.3 cm - 45 cm                                         |
| SEAT-TO-GROUND<br>HEIGHT                 | 52 cm - 55.9 cm                                         |
| GROUND<br>CLEARANCE <sup>5</sup>         | 7.6 cm at frame                                         |

|                                               |                                                                                 |
|-----------------------------------------------|---------------------------------------------------------------------------------|
| OVERALL WEIGHT (NOT INC BATTERY) <sup>2</sup> | 39.4 kg                                                                         |
| WEIGHT OF HEaviest PIECE                      | 15.4 kg (front section)                                                         |
| SUSPENSION                                    | N/A                                                                             |
| 3W/4W OPTION                                  | 4W                                                                              |
| FRONT TYRES                                   | 8" solid                                                                        |
| REAR TYRES                                    | 9" solid                                                                        |
| BATTERY REQUIREMENTS <sup>4</sup>             | (2) 18Ah                                                                        |
| BATTERY CHARGER                               | Off-board, 2A                                                                   |
| BATTERY WEIGHT                                | 6 kg each                                                                       |
| COLOUR OPTIONS <sup>6</sup>                   | <span style="color: red;">■</span> Red <span style="color: blue;">■</span> Blue |

1. Varies with user weight, terrain type, battery amp hour (Ah), battery charge, battery condition and tyre condition.
2. Includes standard seat weight.
3. Width of base (not including seat).
4. Deep cycle (AGM or gel cell type recommended)
5. Does not account for anti-tip clearance.
6. All shroud panels included

**NOTE:** All specifications subject to change without notice. The information contained herein is correct at the time of publication; we reserve the right to alter specifications without prior notice. Speed and range vary with user weight, terrain type, battery charge, battery condition and tyre pressure. Due to manufacturing tolerances and continual product improvement, length, width, turning radius and ground clearance can be subject to variance of 3%